FOR ANY EMERGENCY, 24 HOURS / 7 DAYS, CALL: 1-800-654-6911 (OUTSIDE

USA: 1-423-780-2970)
FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTREC®: USA: 1-800-424-9300 (OUTSIDE USA: 1-703-527-3887)

FOR ALL SDS QUESTIONS & REQUESTS, CALL: 1-800-511-MSDS (OUTSIDE

USA: 1-423-780-2347)

PRODUCT NAME: LEISURE TIME LEAK SEAL

# **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Supplier REVISION DATE: 05/26/2015

Leisure Time SUPERCEDES: 05/27/2009 1400 Bluegrass Lakes Parkway ,

Alpharetta, GA, 30004 MSDS Number: 000000024521

SYNONYMS:
CHEMICAL FAMILY: None

Telephone: +17705215959
Telefax: +17705215959
Web: www.poolspacare.com

CHEMICAL PAMILT:

DESCRIPTION / USE
FORMULA:

None established
None established

Manufacturer Advantis Technologies 1200 Bluegrass Lakes Parkway Alpharetta, GA 30004

United States of America

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Specific target organ toxicity - : Category 3 (Re

single exposure

y - : Category 3 (Respiratory system)

**GHS Label element** 

LEISURE TIME LEAK SEAL

REVISION DATE: 05/26/2015 Page 1 of 9

Hazard pictograms :





Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements : **Prevention:** 

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER

or doctor/ physician if you feel unwell. Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or

doctor/ physician if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER

or doctor/ physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS OR CHEMICAL NAMECAS #% RANGEsodium silicate1344-09-830 - 40

LEISURE TIME LEAK SEAL

REVISION DATE: 05/26/2015 Page 2 of 9

# **SECTION 4. FIRST AID MEASURES**

Inhalation: IF INHALED: Remove individual to fresh air. Seek medical attention if breathing

becomes difficult or if respiratory irritation develops. If not breathing, give artificial

respiration. Call for medical assistance.

Skin Contact: IF ON SKIN: Immediately flush skin with plenty of water for 15 minutes. If clothing

comes in contact with the product, the clothing should be removed immediately and laundered before re-use. Seek medical attention if irritation develops.

Eye Contact: IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes.

Seek medical attention immediately.

Ingestion: IF SWALLOWED: Call a physician immediately. DO NOT induce vomiting unless

directed to do so by a physician. Never give anything by mouth to an unconscious

person.

## **SECTION 5. FIREFIGHTING MEASURES**

Flammability Summary (OSHA): The product is not flammable., Not combustible., The substance or

mixture is not classified as pyrophoric., Not explosive

Flammable Properties

Flash Point: Not applicable

Fire / Explosion Hazards: Reacts with most metals to form flammable hydrogen gas. Extinguishing Media: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Fire Fighting Instructions: Use water spray to cool unopened containers. In case of fire, use

normal fire-fighting equipment and the personal protective

equipment recommended in Section 8 to include a NIOSH approved

self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Protection for Emergency Use th

Situations:

Use the personal protective equipment recommended in Section 8 and a NIOSH approved self-contained breathing apparatus.

**Spill Mitigation Procedures** 

Air Release: Vapors may be suppressed by the use of water fog.

Water Release: If the product contaminates rivers and lakes or drains inform

respective authorities.completely miscible

Land Release: Contain spillage, soak up with non-combustible absorbent material,

(e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).Do not contaminate ponds, waterways or ditches with

chemical or used container.

Additional Spill Information: Prevent further leakage or spillage if safe to do so. Use personal

protective equipment as required. Evacuate personnel to safe areas.

LEISURE TIME LEAK SEAL

REVISION DATE: 05/26/2015 Page 3 of 9

# **SECTION 7. HANDLING AND STORAGE**

Handling: Do not take internally. Avoid contact with skin, eyes and clothing. If

in eyes or on skin, rinse well with water. Avoid breathing vapours,

mist or gas.

Storage: Store in a cool, dry and well ventilated place. Isolate from

incompatible materials. Do not freeze.

Incompatible Materials for Storage: Refer to Section 10, "Incompatible Materials."

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Ventilation beyond that of general exhaust is not normally required. No

exposure limits exist for the constituents of this product.

Protective Equipment for Routine Use of Product

Respiratory Protection: Respiratory protection not normally needed., If vapors, mists or aerosols are

generated, wear a NIOSH approved respirator., NIOSH approved half-face air purifying respirator with an N95 filter. Air purifying respirators should not

be used in oxygen deficient or IDLH atmospheres or if exposure

concentrations exceed ten (10) times the published limit.

Skin Protection : Avoid contact with skin. Impervious gloves Eye Protection: Chemical resistant goggles must be worn.

Protective Clothing Type: impervious clothing

General Protective Ensure that eyewash stations and safety showers are close to the

Measures: workstation location.

### Components with workplace control parameters

no data available

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical State: liquid
Form No data.
Color: No data.
Odor: No data.

Molecular Weight: None established pH: 10.0 - 12.0

Boiling Point: 212 °F (100 °C)

Melting point/freezing 32 -

point

32 - 50 °F (0 - 10 °C)

Density Not applicable

LEISURE TIME LEAK SEAL

REVISION DATE: 05/26/2015 Page 4 of 9

Bulk Density: ()

no data available

Vapor Pressure: 32 hPa

Vapor Density: no data available Viscosity: no data available Solubility in Water: completely miscible

Partition coefficient n-

octanol/water:

No data

Evaporation Rate: No data
Oxidizing: None established

Volatiles, % by vol.:

VOC Content This product does not contain any chemicals listed under the U.S.

Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489). This product does not contain any VOC exemptions

listed under the U.S. Clean Air Act Section 450.

HAP Content Not applicable

# **SECTION 10. STABILITY AND REACTIVITY**

Stability and Reactivity Summary: Stable under normal conditions.

Conditions to Avoid: Heat, Avoid freezing. Chemical Incompatibility: Acids, Metals, alcohols

Hazardous Decomposition Products: Hydrogen, by reaction with metals

Decomposition Temperature: No data

# **SECTION 11. TOXICOLOGICAL INFORMATION**

Component Animal Toxicology

Oral LD50 value:

sodium silicate LD50 = 1,960 mg/kg Rat

Component Animal Toxicology

Dermal LD50 value:

sodium silicate LD50 > 4,640 mg/kg Rabbit

Component Animal Toxicology

Inhalation LC50 value:

sodium silicate no data available

**Product Animal Toxicity** 

<u>Oral LD50 value</u>: LD50 = 1,960 mg/kg Rat Dermal LD50 value: LD50 > 4,640 mg/kg Rabbit

Inhalation LC50 no data available

value:

Skin Irritation: Severe skin irritant

LEISURE TIME LEAK SEAL

REVISION DATE: 05/26/2015 Page 5 of 9

Eye Irritation: Severe eye irritant

Skin Sensitization: This material is not known or reported to be a skin or respiratory sensitizer.

Acute Toxicity: This product is severely irritating to skin, eyes and mucous membranes. Prolonged

contact with the eyes may result in a possible corrosive effect.

Subchronic / Chronic

Toxicity:

Not known or reported to cause subchronic or chronic toxicity.

Reproductive and

Not known or reported to cause reproductive or developmental toxicity.

**Developmental Toxicity:** 

Mutagenicity: Not known or reported to be mutagenic.

Carcinogenicity: This product is not known or reported to be carcinogenic by any reference

source including IARC, OSHA, NTP or EPA.

# **SECTION 12. ECOLOGICAL INFORMATION**

Overview: Slightly toxic to fish and other aquatic organisms.

Ecological Toxicity Values for: sodium silicate

Gambusia affinis (Mosquito fish) - static test 96 h LC50 = 1,800 - 2,320 mg/l

Lepomis macrochirus (Bluegill - 96 h LC50 = 301 - 478 mg/l

sunfish)

Fish, fresh water - semi-static test 96 h LC50 = 3,185 mg/l

(brachydaniorerio)

Daphnia magna (Water flea) - static test 48 h LC50= 494 mg/l

Ceriodaphnia dubia - 48 h EC50= 33.53 mg/l

## **SECTION 13. DISPOSAL CONSIDERATIONS**

CARE MUST BE TAKEN TO PREVENT ENVIRONMENTAL CONTAMINATION FROM THE USE OF THE MATERIAL. THE USER OF THE MATERIAL HAS THE RESPONSIBILITY TO DISPOSE OF UNUSED MATERIAL, RESIDUES AND CONTAINERS IN COMPLIANCE WITH ALL RELEVANT LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS REGARDING TREATMENT, STORAGE AND DISPOSAL FOR HAZARDOUS AND NONHAZARDOUS WASTES.

Waste Disposal Summary: If this product becomes a waste, it DOES NOT meet the criteria of a

hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste of Subpart C, nor is it listed as a hazardous waste under Subpart D.As a nonhazardous liquid waste, it should be disposed of in accordance with local, state

LEISURE TIME LEAK SEAL

REVISION DATE: 05/26/2015 Page 6 of 9

and federal regulations.

# **SECTION 14. TRANSPORT INFORMATION**

DOT

UN number : 3266

Description of the goods : Corrosive liquid, basic, inorganic, n.o.s.

: (Silicic acid, sodium salt)

Class : 8
Packing group : III
Labels : 8
Emergency Response : 154

Guidebook Number

**TDG** 

UN number : 3266

Description of the goods : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

(Silicic acid, sodium salt)

Class : 8 Packing group : III Labels : 8

**IATA** 

UN number : 3266

Description of the goods : Corrosive liquid, basic, inorganic, n.o.s.

(Silicic acid, sodium salt)

Class : 8
Packing group : III
Labels : 8
Packing instruction (cargo : 856

aircraft)

Packing instruction : 852

(passenger aircraft)

Packing instruction : Y841

(passenger aircraft)

**IMDG-CODE** 

UN number : 3266

Description of the goods : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

(Silicic acid, sodium salt)

Class : 8
Packing group : III
Labels : 8
EmS Number 1 : F-A
EmS Number 2 : S-B

# **SECTION 15. REGULATORY INFORMATION**

LEISURE TIME LEAK SEAL

REVISION DATE: 05/26/2015 Page 7 of 9

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **SARA 302**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### **SARA 313**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

#### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

#### **US State Regulations**

Massachusetts Right To Know

No components are subject to the Massachusetts Right to

Know Act.

Pennsylvania Right To Know

Silicic acid, sodium salt 1344-09-8

**New Jersey Right To Know** 

Silicic acid, sodium salt 1344-09-8

## California Prop 65

REVISION DATE: 05/26/2015 Page 8 of 9

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### The components of this product are reported in the following inventories:

TSCA : The components of this product are listed on the TSCA

Inventory of Existing Chemical Substances.

Sodium Silicate Solution 40B

#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

# **SECTION 16. OTHER INFORMATION**

SECTIONS REVISED: First formulated version in SAP.

Major References : Available upon request.

THIS MATERIAL SAFETY DATA SHEET (MSDS) HAS BEEN PREPARED IN COMPLIANCE WITH THE FEDERAL OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200. THE INFORMATION IN THIS MSDS SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. ARCH CHEMICALS BELIEVES THIS INFORMATION TO BE RELIABLE AND UP TO DATE AS OF THE DATE OF PUBLICATION BUT, MAKES NO WARRANTY THAT IT IS. ADDITIONALLY, IF THIS MSDS IS MORE THAN THREE YEARS OLD, YOU SHOULD CONTACT ARCH CHEMICALS MSDS CONTROL AT THE PHONE NUMBER ON THE FRONT PAGE TO MAKE CERTAIN THAT THIS DOCUMENT IS CURRENT.

LEISURE TIME LEAK SEAL REVISION DATE: 05/26/2015